





單投標準型表前開關

型 名	KS-100		KS-200		KS-300		KS-400		KS-500		
外觀											
額定電流 (A)	100		200		300		400		500		
極 數 (P)	2	3	2	3	2	3	2	3	2	3	
最高使用電壓(V)AC	600V										
 外型及安裝尺寸 mm	a	110	110	110	180	120	190	138	220	180	290
	b	110		170		180		210		270	
	c	60		75		75		85		120	
	aa	38		65		70		80		110	
	bb	65		125		128		133		200	
材 料 質 量	纖維・大理石										
備 註	訂製品：3P1600A 以上及 4P 各規格價格另計										
單價 (每 A/元)											

型 名	KS-600		KS-800		KS-1000		KS-1200		KS-2000	
外觀										
額定電流 (A)	600		800		1000		1200		1600-2000	
極 數 (P)	2	3	2	3	2	3	2	3	3	
最高使用電壓(V)AC	600V									
 外型及安裝尺寸 mm	a	180	290	180	290	180	290	180	290	340
	b	270		270		270		270		350
	c	120		120		120		120		130
	aa	110		110		110		110		130
	bb	200		200		200		200		270
材 料 質 量	纖維・大理石									
備 註	訂製品：3P1600A 以上及 4P 各規格價格另計									
單價(每 A/元)										



雙投標準型表前開關

型 名	KS-100		KS-200		KS-300		KS-400		KS-500		
外觀											
額定電流 (A)	100		200		300		400		500		
極 數 (P)	2	3	2	3	2	3	2	3	2	3	
最高使用電壓(V)A.C	600V										
 外型及安裝尺寸 mm	a	112	112	120	180	120	180	140	220	180	280
	b	195		280		300		350		420	
	c	60		75		75		85		120	
	aa		38		65		72		82		110
	bb	150		190		195		215		272	
材 料 質 量	電木										
備 註	訂製品：3P1600A 以上及 4P 各規格價格另計										
單價 (每 A/元)											

型 名	KS-600		KS-800		KS-1000		KS-1200		KS-2000	
外觀										
	600		800		1000		1200		1600-2000	
	2	3	2	3	2	3	2	3	3	
	最高使用電壓 (V)A.C									
600V										
 外型及安裝尺寸 mm	a	180	280	180	280	180	280	180	280	340
	b	420		420		420		420		610
	c	120		120		120		120		130
	aa		110		110		110		110	130
	bb	272		272		272		272		540
材 料 質 量	電木									
備 註	訂製品：3P1600A 以上及 4P 各規格價格另計									
單價 (每 A/元)										